

abfrage icinga vars

- tags an hosts abfragen:

```
#!/bin/sh
#set -x

for host in $(curl -k -s \
  -u 'root:8b032571f6928751' \

'https://kienm23.web.verdi.int:5665/v1/objects/hosts?attrs=name&filter=match(%22kien*%22,host.name)' \
  | jq -r '.results[].name'); do

echo ${host}
curl -k -s \
  -u 'director_api:mU54IiUVBQI-4kJfaQIw' \
  -H 'Accept: application/json' \
  "https://kienm23.web.verdi.int/icingaweb2/director/host?name=${host}" \
  | jq -r '.vars.verdi_service_tags' |grep maillog
# | jq -r '.vars.location'

#curl -k -s \
# -u director_api:mU54IiUVBQI-4kJfaQIw \
# -H 'Accept: application/json' \
# 'https://kienm23.web.verdi.int/icingaweb2/director/host?name=kienm23.web.verdi.int'| jq -
# r '.vars.location'

done
```

- abfrage-boolean-vars-nm21.sh

```
# Abfrage eines boolean Wertes.
# Abfrage aller hosts mit "host.vars.verdi_agent == true"

#!/bin/sh
# set -x
```

```

curl -k -s \
  -u 'IcingaWeb2:0kFTxzQyHCsBRDEAtt' \
  -H 'Accept: application/json' \
  -H 'X-HTTP-Method-Override: GET' \
  -X POST \
  'https://blnpgm21.verdi.int:5665/v1/objects/hosts' \
  -d '{
    "attrs": ["name", "vars"],
    "filter": "host.vars.verdi_agent == enabled",
    "filter_vars": {
      "enabled": true
    },
    "pretty": true
  }' | jq -r '.results[].name';

```

- abfrage-boolean-vars-nm90.sh

```

# Abfrage eines boolean Wertes.
# Abfrage aller hosts mit "host.vars.verdi_agent == true"

#!/bin/sh
# set -x
curl -k -s \
  -u 'IcingaWeb2:mjTZ0fl6b6CZbIDbVM4A' \
  -H 'Accept: application/json' \
  -H 'X-HTTP-Method-Override: GET' \
  -X POST \
  'https://blnpgm90.verdi.int:5665/v1/objects/hosts' \
  -d '{
    "attrs": ["name", "vars"],
    "filter": "host.vars.verdi_agent == enabled",
    "filter_vars": {
      "enabled": true
    },
    "pretty": true
  }' | jq -r '.results[].name';

```

- abfrage-text-vars-nm90.sh

```

# Abfrage eines boolean Wertes.
# Abfrage aller hosts mit "host.vars.verdi_agent == true"

#!/bin/sh
# set -x
curl -k -s \
  -u 'IcingaWeb2:mjTZ0fl6b6CZbIDbVM4A' \
  -H 'Accept: application/json' \
  -H 'X-HTTP-Method-Override: GET' \
  -X POST \
  'https://blnpgm90.verdi.int:5665/v1/objects/hosts' \
  -d '{
    "attrs": ["name", "vars"],
    "filter": "match(pattern, host.vars.os)",
    "filter_vars": {
      "pattern": "linux"
    },
    "pretty": true
  }' | jq -r '.results[].name';

# Beispiele:
# -d '{
#   "attrs": ["name", "vars"],
#   "filter": "match(pattern, host.vars.vmware_name)",
#   "filter_vars": {
#     "pattern": "kienaa94"
#   },
#   "pretty": true
# }' | jq -r '.results[].name';

```

- abfrage-txt-vars-verdi_service_tags-nm21.sh

```

# Abfrage eines boolean Wertes.
# Abfrage aller hosts mit "host.vars.verdi_agent == true"

#!/bin/sh
# set -x
curl -k -s \
  -u 'IcingaWeb2:0kFTxzQyHCsBRDEAtt' \
  -H 'Accept: application/json' \
  -H 'X-HTTP-Method-Override: GET' \

```

```
-X POST \
'https://blnpgm21.verdi.int:5665/v1/objects/hosts' \
-d '{
  "attrs": ["name", "vars"],
  "filter": "match(pattern, host.vars.verdi_service_tags)",
  "filter_vars": {
    "pattern": "verdi.de"
  },
  "pretty": true
}' | jq -r '.results[].name';
```

Beispiele:

```
# -d '{
#   "attrs": ["name", "vars"],
#   "filter": "match(pattern, host.vars.vmware_name)",
#   "filter_vars": {
#     "pattern": "kienaa94"
#   },
#   "pretty": true
# }' | jq -r '.results[].name';
```

Erstellt: 2026-10-08 07:04:43 UTC von thomas

Zuletzt aktualisiert: 2026-10-08 07:47:04 UTC von thomas